

RESURVEY PORTION WEST BOUNDARY T. 21 S., R. 10 W.

CHAINS

4.70 Top of spur, slopes SW; descend NW slope 75 ft. to  
 10.80 Ravine, course SW; ascend S slope 170 ft. to  
 14.70 Top of spur, slopes SW; descend NW slope 70 ft. to  
 16.85 Ravine, course W; ascend S slope 285 ft. to  
 26.20 Top of spur, slopes W; descend NW slope 30 ft. to  
 30.50 Head of ravine, course SW; ascend S slope 100 ft. to  
 32.75 Apportioned distance

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
 the ground, for  $\frac{1}{4}$  Sec. cor. of Sec. 24 only, with  
 brass cap marked

$\frac{1}{4}$   
 S24  
 1919

from which

A Fir, 26 ins. diam., bears S.59\*W., 176 lks.  
 dist., marked  $\frac{1}{4}$  S 24 B T.

A Fir, 6 ins. diam., bears N.58\*W., 37 lks.  
 dist., marked  $\frac{1}{4}$  S 24 B T.

Continue ascent of S. slope 120 ft. to

34.10 Top of ridge, bears E and W; descend 250 ft. to  
 39.75 Creek, 1 lk. wide, course E; ascend 8 ft. to  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
 the ground, for  $\frac{1}{4}$  Sec. cor. of Sec. 19 only, with  
 brass cap marked

$\frac{1}{4}$   
 S19  
 1919

from which

A Fir, 16 ins. diam., bears N.31\*E., 45 lks.  
 dist., marked  $\frac{1}{4}$  S 19 B T.

A Fir, 18 ins. diam., bears S.11\*E., 118 lks.  
 dist., marked  $\frac{1}{4}$  S 19 B T.

Continue ascent 175 ft. to

45.85 Summit of ridge, bears E and W; descend NW slope 480  
 ft. to  
 61.10 Creek, 1 lk. wide, course NW; ascend SW slope 60 ft. to