

RESURVEY PORTION WEST BOUNDARY T. 21 S., R. 10 W.

CHAINS

63.35 Top of spur, slopes W; descend N slope 110 ft. to  
 68.10 Stream, 1 lk. wide, course W; ascend 30 ft. to  
 69.50 Intersect the old cor. of Secs. 13, 18, 19 and 24, which  
 is a Fir, 40 ins. diam., marked and witnessed as  
 described by the Surveyor General. I obliterate the  
 marks on the NE and SE bearing trees and change this  
 corner to refer to Secs. 13 and 24 only,

From this corner

N.0°54'W., resurveying the W. bdy. of Sec. 19.

Ascend steep S. slope 30 ft. to

.80 Top of spur, slopes SW; descend NW slope 140 ft. to

10.50 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in  
 the ground, for cor. of Secs. 18 and 19, with brass  
 cap marked.

	T21S
	S18
	S19
	R10W
1919	

from which

A Fir, 36 ins. diam., bears N.27°E., 76 lks. dist.  
 marked T 21 S R 10 W S 18 B T.

A Hemlock, 24 ins. diam., bears S.83°E., 21 lks.  
 dist., marked T 21 S R 10 W S 19 B T.

Land, mountainous.

Soil, shallow sandy loam and vegetable mold; 2nd and  
 3rd rate.

Timber, Fir, Hemlock, Maple and Alder.

Undergrowth, Salmonberry, Vinemaple and Salal.

---

N.0°54'W., resurveying the W bdy. of Sec. 18.

Over mountainous land, through heavy timber and dense  
 undergrowth, descending 51 ft. to

1.05 Creek, 4 lks. wide, course NE; ascend along E. slope  
 40 ft. to

4.40 Top of ascent; descend along E. slope 110 ft. to