

RESURVEY PORTION WEST BOUNDARY T. 21 S., R. 10 W.

CHAINS

15.80 Creek, 6 lks. wide, course NW; ascend SW slope 300 ft. to
 30.03 Apportioned distance

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 13 only, with
 brass cap marked

$\frac{1}{4}$
 S13
 1919

from which

A Hemlock, 8 ins. diam., bears S.70*W., 12 lks.
 dist., marked $\frac{1}{4}$ S 13 B T.

A Fir, 18 ins. diam., bears N.65*W., 6 lks. dist.,
 marked $\frac{1}{4}$ S 13 B T.

Continue ascent 80 ft. to

33.20 Top of spur, slopes W; descend NW slope 245 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 18 only, with
 brass cap marked

$\frac{1}{4}$
 S18
 1919

from which

A Hemlock, 14 ins. diam., bears N.62*E., 30 lks.
 dist., marked $\frac{1}{4}$ S 18 B T.

A Cedar, 24 ins. diam., bears S.23*E., 8 lks.
 dist., marked $\frac{1}{4}$ S 18 B T.

Continue descent 195 ft. to

46.25 Stream, 1 lk. wide, course W; continue descent over
 creek bottom 10 ft. to

47.25 Stream, 10 lks. wide, course NW; ascend SW slope 300 ft.
 to

60.90 Top of ridge, bears NW and SE; descend 180 ft. to

61.55 Draw, course NW; ascend SW slope 60 ft. to

62.85 Top of spur, slopes NW; descend N. slope 215 ft. to

70.57 Intersect the old cor. of Secs. 7, 12, 13 and 18, which
 is a Cedar, 60 ins. diam., marked and witnessed as
 described by the Surveyor General.