

RESURVEY PORTION NORTH BOUNDARY T. 21 S. R. 10 W.

CHAINS

reference to the old SE bearing tree. I obliterate marks on this tree and at the exact cor. point set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 35 only, with brass cap marked

$\frac{1}{4}$ S35
1919

from which

An Alder, 10 ins. diam., bears N.62*E., 21 lks. dist.; marked $\frac{1}{4}$ S 35 B T.

A Wild Cherry, 10 ins. diam., bears N.9*W., 55 lks. dist., marked $\frac{1}{4}$ S 35 B T.

From this corner

N.87*28'E., resurveying the N Bdy. of Sec. 2.

Ascend gradually.

0.21

(40.00 chs. departure from the cor. of Secs. 1 and 2)
Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 2 only, with brass cap marked

$\frac{1}{4}$ S2
1919

from which

A Wild Cherry, 12 ins. diam., bears S.14*E., 30 lks. dist., marked $\frac{1}{4}$ S 2 B T.

A Maple, 6 ins. diam., bears S.7*W., 10 lks. dist., marked $\frac{1}{4}$ S 2 B T.

Ascend W slope 90 ft. to

7.75

Top of spur ridge, bears N and S; slopes S; descend E slope 430 ft. to

32.75

Foot of descent; ascend W slope 115 ft. to

35.45

Top of spur, slopes SW; thence along S slope.

38.91

Intersect the old cor. of Secs. 1, 2, 35 and 36, which is a decayed post, marked and witnessed as described by the Surveyor General. I change this cor. to refer to Secs. 35 and 36 only and obliterate the marks on