

## RESURVEY PORTION NORTH BOUNDARY T. 21 S., R. 10 W.

CHAINS		
	160 ft. to	
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor. of Sec. 1 only, with brass cap marked	
	$\frac{1}{4}$ S1 1919	
	from which	
	A Fir, 48 ins. diam., bears S.73*E., 27 lks. dist., marked $\frac{1}{4}$ S 1 B T.	
	A Hemlock, 9 ins. diam., bears S.36*W., 44 lks. dist., marked $\frac{1}{4}$ S 1 B T.	
	Descend NE slope 16 ft. to	
41.15	Intersect the old $\frac{1}{4}$ Sec. cor., which is a badly decayed post, marked and witnessed as described by the Surveyor General. I obliterate marks on the bearing tree referring to Sec. 1 and change this cor. to refer to Sec. 36 only and alongside the old cor. set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 36 only, with brass cap marked	
	$\frac{1}{4}$ S36 1919	
	from which	
	A Wild Cherry, 10 ins. diam., bears N.26*E., 38 lks. dist., marked $\frac{1}{4}$ S 36 B T (New B.T.).	
	An Alder, 12 ins. diam., bears N.30*W., 10 lks. dist., marked $\frac{1}{4}$ S 36 B T (Old B.T.)	
	From this corner	
	N.89*33'E., resurveying the N bdy. of Sec. 1.	
	Descend E slope 40 ft. to	
0.80	Ravine, course N; ascend steep NW slope 175 ft. to	
8.55	Top of spur, slopes N; descend NE slope 40 ft. to	
9.40	Ravine, stream 1 lk. wide, course N; ascend NW slope 70 ft. to	
11.20	Top of spur, slopes NE; descend E slope 20 ft. to	