

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

11.40 Top of spur, slopes SE; descend E slope 80 ft. to  
 13.50 Ravine, course SE; ascend W slope 150 ft. to  
 19.20 Top of ridge, bears NW and SE; descend over N slope  
 140 ft. to  
 31.00 Ravine, course N.25\*W; ascend W slope 80 ft. to  
 33.20 Top of spur, slopes N; descend NE slope 35 ft. to  
 36.60 Ravine, course N.20\*W., ascend W slope 110 ft. to  
 38.60 Top of spur, slopes N; descend 20 ft. to  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
 the ground, for  $\frac{1}{4}$  Sec. cor., with brass cap marked

$\frac{1}{4}$  S23  
 S26  
 1919

from which

An Alder, 16 ins. diam., bears N.40\*E., 45 lks.  
 dist., marked  $\frac{1}{4}$  S 23 B T.

An Alder, 20 ins. diam., bears S.26\*E., 32 lks.  
 dist., marked  $\frac{1}{4}$  S 26 B T.

Continue descent 20 ft. to

40.45 Ravine, course N.35\*W; ascend W slope 100 ft. to  
 42.50 Top of spur, slopes N.10\*W., descend NE slope 340 ft. to  
 51.75 Ravine, course N; ascend NW slope 120 ft. to  
 54.40 Top of spur, slopes N; descend NE slope 70 ft. to  
 57.10 Ravine, course N; ascend NW slope 140 ft. to  
 60.65 Top of spur, slopes N; descend NE slope 340 ft. to  
 70.50 Dry bed of stream, course N; thence across flat.  
 71.45 Dry bed of stream, course NW; ascend SW slope 210 ft. to  
 77.10 Top of spur, slopes S; descend SE slope 30 ft. to  
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in  
 the ground, for cor. of Secs. 23, 24, 25 and 26, with  
 brass cap marked

T21S R10W  
 S23 | S24  
 S26 | S25  
 1919

from which

A Maple, 8 ins. diam., bears N.21\*E., 45 lks.  
 dist., marked T 21 S R 10 W S 24 B T.