

## SUBDIVISIONS, T. 21 S., R. 10 W.

## CHAINS

South, on sectional guide meridian, bet. Secs. 35 and 36.  
 Descend SW slope, through heavy timber and dense under-  
 growth, 170 ft. to  
 5.00 Dry bed of stream, course NW; ascend NE slope 520 ft.  
 to spur.  
 11.80 Rock bed ravine, course NE; ascend NW slope.  
 19.20 Top of spur, slopes NE; ascend along E slope 310 ft.  
 to ridge.  
 27.70 Draw, course NE; ascend N slope.  
 35.40 Top of ridge, bears NW and SE; descend SW slope 100 ft.  
 to corner.  
 37.90 Draw, course W; along SW slope.  
 39.00 Small spur, slopes SW; descend S slope.  
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
 the ground, for  $\frac{1}{4}$  Sec. cor., with brass cap marked

$\frac{1}{4}$   
 S35 | S36  
 1919

from which

A Fir, 16 ins. diam., bears N.6°E., 10 lks. dist.,  
 marked  $\frac{1}{4}$  S 36 B T.

A Fir, 24 ins. diam., bears N.60°W., 12 lks. dist.,  
 marked  $\frac{1}{4}$  S 35 B T.

Descend SW slope 205 ft. to  
 45.70 Ravine, course W.  
 46.20 Ravine, course NW; ascend NE slope 360 ft. to  
 54.45 Top of spur, slopes S.80°W; ascend along W slope 15 ft. to  
 57.90 Top of spur, slopes W; descend SW slope 360 ft. to  
 65.00 Ravine, course SW; ascend along W slope 20 ft. to  
 66.50 Top of spur, slopes SW; descend SW slope 140 ft. to  
 70.50 Rocky gorge, course NW; ascend NE slope 480 ft. to  
 88.06 Intersect the S bdy. of the Tp., at the cor. of Secs. 35  
 and 36, previously described.

Land, mountainous.  
 Soil, shallow light loam; 2nd rate.  
 Timber, Fir, Cedar and Hemlock.