

County Surveyor's Record, Douglas County, Oregon

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

- 1.15 Wasson Creek, 50 lks. wide, course W; ascend gradually along W slope 20 ft. to
- 9.70 Small stream, 4 lks. wide, course W; ascend SW slope 610 ft. to corner.
- 26.95 Top of spur, slopes SE; ascend along E slope.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ Sec. corner, with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ S11 | S12 \\ \hline 1919 \end{array}$$

from which

A Fir, 8 ins. diam., bears S.7*E., 20 lks. dist., marked $\frac{1}{4}$ S 12 B T.

A Fir, 18 ins. diam., bears N.42*W., 17 lks. dist., marked $\frac{1}{4}$ S 11 B T.

Ascend along E slope 40 ft. to

- 44.05 Top of ridge, bears NE and SW; continue ascend along W. slope 50 ft. to
- 47.80 Top of same ridge, bears NW and SE; ascend along E and SE slope 115 ft. to
- 58.90 Top of ridge, bears NE and SW; descend NW slope 280 ft. to
- 66.10 Ravine, course W; ascend SW slope 125 ft. to
- 68.80 Top of spur, slopes W; descend NW slope 225 ft. to
- 73.15 Small stream, 2 lks. wide, course W; ascend SW slope 230 ft. to
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of Secs. 1, 2, 11 and 12, with brass cap marked

$$\begin{array}{c} T21S R10W \\ S2 | S1 \\ \hline S11 | S12 \\ 1919 \end{array}$$

from which

An Alder, 16 ins. diam., bears N.44*E., 13 lks. dist., marked T 21 S R 10 W S 1 B T.

An Alder, 12 ins. diam., bears S.52*E., 13 lks. dist., marked T 21 S R 10 W S 12 B T.