

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

A Chittem, 6 ins. diam., bears S.66*W., 7 lks. .
dist., marked $\frac{1}{4}$ S 22 B T.

A Chittem, 8 ins. diam., bears N.4*W., 23 lks. .
dist., marked $\frac{1}{4}$ S 22 B T.

From this corner

N.0*36'E., resurveying the line bet. Secs. 22 and 23.

Continue ascent of S slope 40 ft. to

2.02 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ sec. cor. of Sec. 23 only, with
brass cap marked

$\frac{1}{4}$
S23
1919

from which

A Hemlock, 5 ins. diam., bears N.54*E., 29 lks.
dist., marked $\frac{1}{4}$ S 23 B T

A Hemlock, 14 ins. diam., bears S.6*E., 33 lks.
dist., marked $\frac{1}{4}$ S 23 B T.

Continue ascent 255 ft. to

8.95 Top of ascent on E slope; descend NE slope 75 ft. to

15.50 Ravine, course SE; ascend SE slope 265 ft. to

26.05 Top of ridge, bears NE and SW; descend NW slope 110 ft.
to

31.65 Small ravine, course W; ascend SW slope 75 ft. to

34.45 Top of spur, slopes N.80*W., descend N. slope 150 ft. to

37.71 Intersect the point for old cor. of Secs. 14, 15, 22 and
23, located by reference to the old bearing trees,
which are as described by the Surveyor General. I
obliterate marks on the NE and SE bearing trees and
at the exact cor. point set an iron post, 3 ft. long,
2 ins. diam., 24 ins. in the ground, for cor. of Secs.
15 and 22, with brass cap marked

T21S
S15
S22
R10W
1919