


SUBDIVISIONS T. 21 S., R. 10 W.

CHAINS

5.00 Ravine, course NW; ascend 65 ft. to
 6.55 Top of spur, slopes W; descend NW slope 20 ft. to
 11.35 Ravine, course S.10*W; ascend broken SE slope 580 ft. to
 24.70 Top of spur, slopes SW; descend along W slope 150 ft. to
 29.65 Ravine, course SW; ascend S slope 155 ft. to
 32.96 Intersect the old $\frac{1}{4}$ Sec. cor., which is a dead Fir,
 marked and witnessed as described by the Surveyor
 General. I obliterate marks on the old SE bearing
 tree and change this cor. to refer to Sec. 15 only.
 Alongside the old cor. set an iron post, 3 ft. long,
 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ Sec. cor.
 of Sec. 15 only, with brass cap marked




from which

- A Fir, 11 ins. diam., bears S.31*W., 23 lks.
 dist., marked $\frac{1}{4}$ S 15 B T. (New B.T.)
- A Fir, 16 ins. diam., bears N.87 $\frac{1}{2}$ *W., 15 lks.
 dist., marked $\frac{1}{4}$ S 15 B T (Old B.T.)

From this corner

N.1*15*W., resurveying the line bet. Secs. 14 and 15.
 Along W slope.

1.35 Top of ridge, bears NW and SE; descend NE slope 190 ft.
 to
 7.09 (A point 40.00 chs. northing from the cor. of Secs. 14
 and 23)
 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 14 only, with
 brass cap marked



from which

- A Chittem, 8 ins. diam., bears N.67*E., 37 lks.
 dist., marked $\frac{1}{4}$ S 14 B T.
- A Chittem, 6 ins. diam., bears S.42*E., 17 lks.