

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

dist., marked 1/4 S 14 B T.

Continue descent of NE slope 225 ft. to

17.95 Ravine, course E; ascend along E slope 320 ft. to

30.65 Top of spur, slopes NE; descend N slope 295 ft. to

37.24 Intersect the point for old cor. of Secs. 10, 11, 14

and 15, located by reference to the old bearing trees, which are marked as described by the Surveyor General,

except the SW tree has fallen. I obliterate marks on

the NE and SE bearing trees and at the exact cor. point

set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in

the ground, for cor. of secs. 10 and 15, with brass

cap marked

T21S  
S10  
S15  
R10W  
1919

from which

A Maple, 10 ins. diam., bears S.25\*W., 62 lks.

dist., marked T. 21 S R 10 W S 15 B T (New B.T.)

A Cedar, 18 ins. diam., bears N.22\*W., 34 lks.

dist., marked T 21 S R 10 W S 10 B T (Old B.T.)

From this corner

North, bet. Secs. 10 and 14.

Descend NW slope, 105 ft. to

3.05 Stream, 2 lks. wide, course NE; ascend SE slope 70 ft. to

7.25 Top of ascent on E slope; descend gradually along E

slope 50 ft. to

9.86 (A point 80.00 chs. northing from the corner of Secs.

14 and 23)

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in

the ground, for cor. of Secs. 11 and 14, with brass

cap marked

T21S  
S11  
S14  
R10W  
1919

from which