

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

N.0°01'W., bet. Secs. 2 and 3.

Over mountainous land, through heavy timber and dense undergrowth, ascending SW slope 25 ft. to

1.00 Top of ridge, bears NW and SE; descend NE slope 235 ft. to

13.80 Ravine, course NE; ascend SE slope 160 ft. to

27.05 Top of spur, slopes NE; descend NW slope 235 ft. to

32.03 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 3 only, with brass cap marked

$\frac{1}{4}$
S3
1919

from which

A Double Alder, 40 ins. diam., bears S.16°W., 140 lks. dist., marked $\frac{1}{4}$ S 3 B T.

A Cedar, 30 ins. diam., bears N.13°W., 160 lks. dist., marked $\frac{1}{4}$ S 3 B T.

Continue descent of NW slope 65 ft. to

33.40 Stream, 3 lks. wide, course NE; ascend along E slope 15 ft. to

36.10 Top of small spur, slopes E; descend NE slope 60 ft. to

37.65 Small stream, 1 lk. wide, course E; ascend SE slope 80 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 2 only, with brass cap marked

$\frac{1}{4}$
S2
1919

from which

A Fir, 48 ins. diam., bears N.40°E., 30 lks. dist., marked $\frac{1}{4}$ S 2 B T.

An Alder, 16 ins. diam., bears S.20°E., 39 lks. dist., marked $\frac{1}{4}$ S 2 B T.

Continue ascent 20 ft. to