

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS	
	West, on sectional correction line, along N bdy. of Sec. 28.
	Over mountainous land, through heavy timber and dense undergrowth, descending NW slope 285 ft. to
8.50	Head of draw, course NW; ascend NE slope 115 ft. to
12.60	Top of spur, slopes N; descend NW slope 295 ft. to
18.60	Draw, course NW; ascend NE slope 100 ft. to
23.60	Top of spur, slopes NW; descend W slope 200 ft. to
28.20	Creek, 6 lks. wide, course N.10°E., ascend NE slope 160 ft. to
35.50	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ Sec.cor. of Sec. 21 only, with brass cap marked
	<u>$\frac{1}{4}$ S21</u>
	1919
	from which
	A Hemlock, 14 ins. diam., bears N.78°E., 35 lks. dist., marked $\frac{1}{4}$ S 21 B T.
	A Fir, 22 ins. diam., bears N.28°W., 30 lks. dist., marked $\frac{1}{4}$ S 21 B T.
	Ascend gradually 80 ft. to $\frac{1}{4}$ Sec. corner.
38.40	Draw, course NE; ascend SE slope.
40.00	Set a sandstone, 18x10x6 ins. 12 ins. in the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 28 only, marked $\frac{1}{4}$ on S face;
	from which
	A Fir, 18 ins. diam., bears S.28°E., 80 lks. dist., marked $\frac{1}{4}$ S 28 B T.
	A Cedar, 8 ins. diam., bears S.31°W., 79 lks. dist., marked $\frac{1}{4}$ S 28 B T.
	Iron post impracticable.
	Ascend E slope 410 ft. to
49.10	Top of ridge, bears N and S; descend abrupt W slope 245 ft. to
54.20	Head of draw, course W; descend SW slope on N side of draw, 165 ft. to