

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS	
	West, on sectional correction line, bet. Secs. 20 and 29. Over mountainous land, through heavy timber and dense undergrowth, ascending along S slope 15 ft. to
1.90	Top of ascent; descend SW slope 150 ft. to
5.70	Ravine, course S; ascend SE slope 220 ft. to
11.00	Top of small spur, slopes S; descend SW slope 290 ft. to
18.30	Ravine, course S; along S slope.
19.50	Stream, 2 lks. wide, course SE; ascend NE slope 475 ft. to
32.10	Top of spur, slopes SE; descend along general S slope 50 ft. to
34.90	Foot of descent; ascend 75 ft. to
38.00	Top of ascent, bears N and S; descend abrupt W slope 115 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., with brass cap marked
	$\frac{\frac{1}{4} \text{ S20}}{\frac{1}{4} \text{ S29}}$ 1919
	from which
	A Fir, 8 ins. diam., bears N.20*E., 69 lks. dist., marked $\frac{1}{4}$ S 20 B T.
	A Fir, 10 ins. diam., bears S.43*W., 43 lks. dist., marked $\frac{1}{4}$ S 29 B T.
	Descend broken SW slope 145 ft. to
50.10	Stream, 1 lk. wide, in ravine, course SE; ascend NE slope 370 ft. to
58.00	Top of ridge, bears N and S; descend general NW slope 165 ft. to
64.05	Descend general W slope 255 ft. to
80.00	Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of Secs. 19, 20, 29 and 30, with brass cap marked