

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

- 31.30 Ravine, course E; ascend NE slope 105 ft. to
- 33.50 Top of spur, slopes E; descend SE slope 295 ft. to ravine.
- 40.00 Point for $\frac{1}{4}$ Sec. cor. in wash, course SE; where it is impracticable to establish permanent corner.
- 40.40 Ravine, course NE; ascend 30 ft. to
- 41.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for witness cor. to the $\frac{1}{4}$ Sec. cor. with brass cap marked

WC
 $\frac{1}{4}$
 S28 | S27
 1919

from which

A Cedar, 30 ins. diam., bears S.72*E., 26 lks. dist., marked W C $\frac{1}{4}$ S 27 B T.

An Alder, 10 ins. diam., bears N.79*W., 51 lks. dist., marked W C $\frac{1}{4}$ S 28 B T.

Ascend N slope 430 ft. to

- 49.65 Top of spur, slopes NE; thence along E slope.
- 51.90 Top of spur, slopes E; descend SE slope 200 ft. to
- 59.05 Ravine, course E; ascend N slope 75 ft. to
- 61.40 Top of spur, slopes E; descend SE slope 90 ft. to
- 64.35 Ravine, course E; ascend broken NE slope 465 ft. to
- 78.85 Top of spur, slopes E; descend SE slope 45 ft. to
- 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of Secs. 27, 28, 33 and 34, with brass cap marked

T21S R10W
 S28 | S27
 S33 | S34
 1919

from which

A Fir, 14 ins. diam., bears N.66*E., 27 lks. dist., marked T 21 S R 10 W S 27 B T.

A Fir, 12 ins. diam., bears S.12*E., 7 lks. dist., marked T 21 S R 10 W S 34 B T.