

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

of Secs. 15, 16, 21 and 22, with brass cap marked

T21S R10W  
 $\frac{S16 | S15}{S21 | S22}$   
 1919

from which

- A Hemlock, 30 ins. diam., bears N.76 $\frac{1}{2}$ \*E., 36 lks. dist., marked T 21 S R 10 W S 15 B T (Old B.T.)
- An Alder, 14 ins. diam., bears S.36 $\frac{1}{2}$ \*E., 40 lks. dist., marked T 21 S R 10 W S 22 B T (Old B.T.)
- An Alder, 36 ins. diam., bears S.30 $\frac{1}{2}$ \*W., 63 lks. dist., marked T 21 S R 10 W S 21 B T (Old B.T.)
- An Alder, 24 ins. diam., bears N.45 $\frac{1}{2}$ \*W., 86 lks. dist., marked T 21 S R 10 W S 16 B T (New B.T.)

Thence

South, bet. Secs. 21 and 22.

Over mountainous land, through heavy timber and dense undergrowth, ascending N slope 255 ft. to

- 7.50 Top of spur, slopes NW; descend along W slope 100 ft. to
- 14.40 Ravine, course W; thence along W slope.
- 21.20 Ravine, course W; ascend along W slope 30 ft. to
- 28.55 Ravine, course W; continue ascent 60 ft. to
- 34.50 Ravine, course NW; ascend N slope 145 ft. to
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  Sec. cor. with brass cap marked

$\frac{1}{4}$   
 $\frac{S21 | S22}{1919}$

from which

- A Fir, 24 ins. diam., bears N.14\*E., 40 lks. dist., marked  $\frac{1}{4}$  S 22 B T.
- A Maple, 12 ins. diam., bears N.45\*W., 40 lks. dist., marked  $\frac{1}{4}$  S 21 B T.

No trace of the old  $\frac{1}{4}$  Sec. corner could be found.

Ascend general NW slope 835 ft. to top of ridge.

- 49.50 Top of spur, slopes NW; along W slope.
- 55.70 Draw, course W; ascend NW slope.