

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

Continue descent 145 ft. to  
 39.45 Canyon, course SW; ascend along S slope 80 ft. to  
 42.20 Top of spur, slopes SW; descend W slope 165 ft. to  
 47.85 Ravine, course SW; ascend along S slope 75 ft. to  
 51.70 Top of spur, slopes SW; descend W slope 225 ft. to  
 56.70 Ravine, course SW; ascend along S slope 100 ft. to  
 60.50 Top of ascent; descend 190 ft. to  
 75.26 Intersect the old cor. of Secs. 9, 10, 15 and 16, which  
 is a sandstone, firmly set, marked and witnessed as  
 described by the Surveyor General, except the old SW  
 bearing tree is dead. Alongside, the old stone set  
 an iron post, 3 ft. long, 2 ins. diam., 24 ins. in  
 the ground, for cor. of Secs. 9, 10, 15 and 16, with  
 brass cap marked

T21S R10W	
S9	S10
S16	S15
1919	

from which

An Alder, 12 ins. diam., bears N.68°E., 80 lks.

dist., marked T 21 S R 10 W S 10 B T.

A Hemlock, 24 ins. diam., bears S.73°E., 19 lks.

dist., marked T 21 S R 10 W S 15 B T. (Old B.T.)

An Alder, 8 ins. diam., bears S.33°W., 26 lks.

dist., marked T 21 S R 10 W S 16 B T.

A Hemlock, 24 ins. diam., bears N.23°W., 36 lks.

dist., marked T 21 S R 10 W S 9 B T.

Land, mountainous.

Soil, rocky loam; 2nd rate.

Timber, Fir, Hemlock, Alder, Cedar and Maple.

Undergrowth, Vinemaple, Huckleberry, Salmonberry, Salal  
 and Fern.

---

N.0°39'E., resurveying the line bet. secs. 9 and 10.

Over mountainous land, through heavy timber and dense  
 undergrowth; descending NW slope 20 ft. to