

SUBDIVISIONS. T. 21 S. R. 10 W.

CHAINS

- 1.45 Wasson Creek, 167 lks. wide, course NE; ascend SE slope
.110 ft. to
- 7.65 Top of spur, slopes E; descend NE slope 115 ft. to .
- 15.45 Wasson Creek, 50 lks. wide, course W; ascend SW slope
.175 ft. to
- 19.15 Top of spur, slopes W; descend NW slope 15 ft. to .
- 21.05 Shallow ravine, course W; ascend SW slope 200 ft. to
- 27.95 Top of spur, slopes W; descend 20 ft. to
- 29.90 Shallow ravine, course W; ascend SW slope 120 ft. to
- 32.80 Top of spur, slopes W; descend NW slope 290 ft. to
- 40.40 Intersect the point for old $\frac{1}{4}$ sec. cor., located by
reference to the old NE bearing tree. At the exact
corner point set an iron post, 3 ft. long, 1 in. diam.,
26 ins. in the ground, for $\frac{1}{4}$ Sec. cor., with brass
cap marked

$\frac{1}{4}$
S9 | S10
1919

from which

An Alder, 24 ins. diam., bears N.10*E., 32 lks.
dist., marked $\frac{1}{4}$ S 10 B T (Old B.T.)

A Chittem, 8 ins. diam., bears N.82*W., 96 lks.
dist., marked $\frac{1}{4}$ S 9 B T (New B.T.)

From this $\frac{1}{4}$ Sec. corner

N.0*43'E., bet. Secs. 9 and 10.

Descend NW slope 35 ft. to

- 1.10 Stream, 2 lks. wide, course W; ascend irregular SW
slope 870 ft. to
- 34.25 Top of spur, slopes SW; descend along W slope 270 ft. to
- 41.08 The apportioned point for cor. of Secs. 3, 4, 9 and 10.
Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of Secs. 3, 4, 9 and 10, with
brass cap marked

T21S R10W
S4 | S3
S9 | S10
1919