

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

19.90 Creek, 5 lks. wide, course SW; ascend N slope 375 ft. to
 27.50 Top of ridge, bears E and W; descend SW slope.
 33.00 Descend SE slope.
 35.20 Ravine, course SW; 305 ft. below ridge; ascend 50 ft. to
 37.00 Top of ascent, bears NE and SW; thence along W slope.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ Sec. corner, with brass cap
 marked

$$\begin{array}{c} \frac{1}{4} \\ S29 \mid S28 \\ 1919 \end{array}$$

from which

A Fir, 18 ins. diam., bears S.9°E., 25 lks. dist.,
 marked $\frac{1}{4}$ S 28 B T.

A Fir, 14 ins. diam., bears S.75°W., 27 lks. dist.,
 marked $\frac{1}{4}$ S 29 B T.

Continue along W slope.

43.20 Top of spur, slopes SW; descend SE slope 290 ft. to
 50.60 Creek, 10 lks. wide, course SW; ascend N slope 595 ft.
 to ridge.
 53.40 Ascend NE slope.
 55.80 Ascend along E slope.
 59.20 Ravine, course NE; ascend N slope.
 66.05 Top of ridge, bears E and W; descend S slope on top of
 rocky spur, 420 ft. to
 75.60 Ravine, course SE; thence along E slope.
 77.50 Descend S slope 100 ft. to
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
 the ground, for cor. of Secs. 28, 29, 32 and 33, with
 brass cap marked

$$\begin{array}{c} T21S R10W \\ S29 \mid S28 \\ \hline S32 \mid S33 \\ 1919 \end{array}$$

from which