

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS	
	From the cor. of Secs. 15, 16, 21 and 22.
	N.87°37'W., resurveying the line bet. Secs. 16 and 21.
	Over mountainous land, through heavy timber and dense undergrowth, descending NW slope 25 ft. to
3.40	Wasson Creek, 172 lks. wide, course S.80°W., thence along creek.
8.15	Same creek, 64 lks. wide, course NW; ascend gradual NE slope 25 ft. to
18.05	Ravine, course NE; continue ascent 100 ft. to
26.25	Ravine, course NE; continue ascent 100 ft. to
29.50	Small ravine, course NE; ascend NE slope 345 ft. to
35.50	Top of spur, slopes N; descend NW slope 95 ft. to
39.18	Apportioned distance, point for $\frac{1}{4}$ Sec. corner in ravine, course NW., where it is impracticable to reestablish $\frac{1}{4}$ Sec. corner.
	Along N slope.
39.68	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for witness cor. to the $\frac{1}{4}$ Sec. cor. with brass cap marked
	$\frac{1}{4} \frac{S16}{S21} WC$ 1919
	from which
	An Alder, 12 ins. diam., bears N.48°W., 38 lks. dist., marked W C $\frac{1}{4}$ S 16 B T.
	A Cedar, 18 ins. diam., bears S.41°E., 69 lks. dist., marked W C $\frac{1}{4}$ S 21 B T.
	Continue along N slope.
40.15	Ravine, course NE; ascend SE slope 545 ft. to
61.50	Top of ridge, bears NE and SW; descend NW slope 450 ft. to
73.60	Ravine, course NW; ascend NE slope 255 ft. to
78.36	Intersect the old cor. of Secs. 16, 17, 20 and 21, which is a stone, marked and witnessed by the old SE bearing tree as described by the Surveyor General. I change this cor. to refer to Secs. 16 and 21 only and