

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

31.20 Ravine, course N.80\*W; ascend SW slope 145 ft. to  
 34.90 Intersect point for old  $\frac{1}{4}$  Sec. cor., located by  
 reference to the old bearing trees, which are marked  
 as described by the Surveyor General. I change this  
 cor. to refer to Sec. 16 only and at the exact cor.  
 point set an iron post, 3 ft. long, 1 in. diam., 26  
 ins. in the ground, for  $\frac{1}{4}$  Sec. cor. of Sec. 16 only,  
 with brass cap marked

$\frac{1}{4}$   
 S16  
 1919

from which

An Alder, 10 ins. diam., bears N.54\*E., 24 lks.  
 dist., marked  $\frac{1}{4}$  S 16 B T.

A Cedar, 18 ins. diam., bears S.85\*E., 10 lks.  
 dist., marked  $\frac{1}{4}$  S 16 B T.

From this  $\frac{1}{4}$  Sec. corner

N.1\*09\*W., resurveying the W bdy. of Sec. 16.

Along W. slope

0.85 Top of spur, slopes W; descend NW slope 205 ft. to  
 5.35 Ravine, course W; ascend SW slope 50 ft. to  
 6.68 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in  
 the ground, for  $\frac{1}{4}$  Sec. cor. of Sec. 17 only, with  
 brass cap marked

$\frac{1}{4}$   
 S17  
 1919

from which

A Fir, 14 ins. diam., bears S.81\*W., 40 lks.  
 dist., marked  $\frac{1}{4}$  S 17 B T.

A Fir, 18 ins. diam., bears N.69\*W., 45 lks.  
 dist., marked  $\frac{1}{4}$  S 17 B T.

Along W slope.

7.00 Top of spur, slopes W; descend NW slope 260 ft. to  
 16.65 Perkins Creek, 56 lks. wide, course NE; ascend SE  
 slope 310 ft. to  
 32.70 Top of spur, slopes E; descend NE slope 75 ft. to