

SUBDIVISIONS: T. 21 S., R. 10 W.

CHAINS

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for  $\frac{1}{4}$  Sec. cor., with brass cap marked

$$\begin{array}{c} \frac{1}{4} \\ \text{S8} \mid \text{S9} \\ \hline 1919 \end{array}$$

from which

An Alder, 12 ins. diam., bears N.11\*E., 74 lks. dist., marked  $\frac{1}{2}$  S 9 B T.

An Alder, 10 ins. diam., bears N.43\*W., 40 lks. dist., marked  $\frac{1}{2}$  S 8 B T.

Continue descent 10 ft. to

39.80 Creek, 8 lks. wide, course E; ascend SW slope 105 ft. to

45.45 Top of spur, slopes SE; descend NE slope 330 ft. to

58.00 Stream, 1 lk. wide, course SE; ascend SE slope 185 ft. to

71.85 Top of spur, slopes E; descend NE slope 285 ft. to

78.14 Intersect the old cor. of Secs. 4, 5, 8 and 9, which is a stone, loosely set, marked and witnessed as described by the Surveyor General. Alongside, the old cor. set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for cor. of Secs. 4, 5, 8 and 9, with brass cap marked

$$\begin{array}{c} \text{T21S R10W} \\ \text{S5} \mid \text{S4} \\ \hline \text{S8} \mid \text{S9} \\ \hline 1919 \end{array}$$

from which

An Alder, 30 ins. diam., bears N.12\*E., 37 lks. dist., marked T 21 S R 10 W S 4 B T (Old B.T.)

A Maple, 30 ins. diam., bears S.8\*E., 77 lks. dist., marked T 21 S R 10 W S 9 B T.

A Cedar, 14 ins. diam., bears S.36\*W., 66 lks. dist., marked T 21 S R 10 W S 8 B T.

A Cedar, 24 ins. diam., bears N.32\*W., 41 lks. dist., marked T 21 S R 10 W S 5 B T.

Land, mountainous.

Soil, rocky loam; 2nd rate.