

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

- 39.79 The corner of Secs. 3, 4, 9 and 10.
 Land, mountainous.
 Soil, shallow rocky sandy loam; 2nd and 3rd rate.
 Timber, Fir, Alder, Maple, Cedar and Hemlock.
 Undergrowth, Salmonberry, Huckleberry and Vinemaple.
-
- From the corner of Secs. 19, 20, 29 and 30.
 S.0°03'E., bet. Secs. 29 and 30.
 Over mountainous land, through heavy timber and dense
 undergrowth, ascending NW slope 188 ft. to ridge.
- 5.65 Top of spur, slopes NW; continue ascent.
- 6.85 Top of spur ridge, bears E and W. slopes W; descend
 S and SE slopes 410 ft. to
- 15.20 Creek, 5 lks. wide, course SW; ascend NW slope 33 ft. to
- 16.85 Top of spur, slopes W; descend SW slope 58 ft. to
- 19.85 Creek, 6 lks. wide, course SW; ascend N slope 480 ft. to
- 31.20 Top of spur, slopes W; descend S slope 307 ft. to
- 37.60 Stream, 3 lks. wide, course W; ascend 70 ft. to
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
 the ground, for $\frac{1}{4}$ Sec. cor., with brass cap marked
- $$\begin{array}{c} \frac{1}{4} \\ \text{S30} | \text{S29} \\ 1919 \end{array}$$
- from which
- A Fir, 13 ins. diam., bears N.85°E., 18 lks.
 dist., marked $\frac{1}{4}$ S 29 B T.
- A Fir, 14 ins. diam., bears S.80°W., 2 lks.
 dist., marked $\frac{1}{4}$ S 30 B T.
- Ascend along W slope 85 ft. to
- 46.05 Draw, course NW; ascend 125 ft. to
- 48.40 Top of ridge, bears E and W; descend along E slope 40
 ft. to
- 50.80 Top of spur, slopes SE; descend S slope 360 ft. to
- 60.15 Creek, 6 lks. wide, course SE; ascend 90 ft. to
- 63.80 Top of spur, slopes E; descend 50 ft. to