

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

65.00 Bottom of descent; ascend 15 ft. to
 66.40 Top of small spur, slopes E; descend S slope 100 ft. to
 70.05 Foot of descent; thence along E slope.
 71.85 Top of spur, slopes E; descend SE slope 125 ft. to
 80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
 the ground, for cor. of Secs. 29, 30, 31 and 32, with
 brass cap marked

T21S R10W	
S30	S29
S31	S32
1919	

from which

A Fir, 6 ins. diam., bears N.23*E., 25 lks. dist.,
 marked T 21 S R 10 W S 29 B T.

A Fir, 12 ins. diam., bears S.5*E., 11 lks. dist.,
 marked T 21 S R 10 W S 32 B T.

A Fir, 10 ins. diam., bears S.88*W., 9 lks. dist.,
 marked T 21 S R 10 W S 31 B T.

A Fir, 10 ins. diam., bears N.27*W., 12 lks. dist.,
 marked T 21 S R 10 W S 30 B T.

Land, mountainous.

Soil, shallow stony sandy loam; 2nd and 3rd rate.

Timber, Fir, Alder, Maple, Cedar and Hemlock.

Undergrowth, Salmonberry, Huckleberry, Rhododendron,
 Vinemaple, Salal and Fern.

East, on a random line, bet. Secs. 29 and 32.

40.00 Set temp. $\frac{1}{4}$ Section corner.

80.00 Intersect N and S line, 35 lks. N of the corner of
 Secs. 28, 29, 32 and 33.

Thence

N.89*45*W., on a true line, bet. Secs. 29 and 32.

Over mountainous land, through heavy timber and dense
 undergrowth, ascending SE slope 110 ft. to

3.70 Top of spur, slopes S; descend 110 ft. to