

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS	
40.00	Set. temp. $\frac{1}{4}$ Sec. corner.
73.05	Intersect W bdy. of the Tp., 21 lks. N of the corner of Secs. 30 and 31. Thence N.89*50'E., on a true line, bet. Secs. 30 and 31. Over mountainous land, through heavy timber and dense undergrowth, over creek bottom.
0.25	Creek, 10 lks. wide, course SE; ascend SW slope.
3.50	Top of spur, slopes S; continue ascent of SW slope..
10.40	Draw, course S; ascend W slope.
13.05	Top of spur, slopes S; 265 ft. above corner; descend SE and E slope 300 ft. to creek.
23.74	Intersect bdy. of H.E.S. No. 129, N.2*15'E., 4.03 chs. from cor. No. 20, which is a stone, firmly set, marked and witnessed as described by the Surveyor General.
25.70	Creek, 10 lks. wide, course S; ascend 300 ft. to $\frac{1}{4}$ Section corner.
30.60	Intersect bdy. of H.E.S. No. 129, N.27*24'W., 5.84 chs. from cor. No. 16, which is a stone, firmly set, marked and witnessed as described by the Surveyor General.
33.05	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ Sec. cor., with brass cap marked $\begin{array}{r} \frac{1}{4} \text{ S30} \\ \frac{1}{4} \text{ S31} \\ \hline 1919 \end{array}$ from which A Fir, 8 ins. diam., bears N.70*W., 87 lks. dist., marked $\frac{1}{4}$ S 30 B T. A Fir, 6 ins. diam., bears S.71*W., 106 lks. dist., marked $\frac{1}{4}$ S 31 B T. Ascend 30 ft. to
34.20	Top of spur, slopes S; descend SE slope 50 ft. to
36.95	Ravine, course S; ascend SW slope 75 ft. to