

## SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS	
0.90	Mouth of ravine, course NW; ascend NW slope 350 ft. to
20.00	Top of spur, slopes N; descend NE slope 150 ft. to
30.20	Ravine, course N; ascend.
32.60	Ravine, course N; ascend steep W slope 175 ft. to
34.92	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ sec. cor., of Sec. 18 only, with brass cap marked
	$\frac{1}{4}$ <u>S18</u> 1919
	from which
	A Fir, 30 ins. diam., bears S.62*E., 17 lks. dist., marked $\frac{1}{4}$ S 18 B T.
	A Cedar, 12 ins. diam., bears S.48*W., 14 lks. dist., marked $\frac{1}{4}$ S 18 B T.
	Ascend NW slope 10 ft. to
35.30	Top of spur, slopes N; descend 20 ft. to
36.40	Ravine, course N; ascend 15 ft. to
37.90	Top of ascent; descend NE slope 90 ft. to
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground, for $\frac{1}{4}$ Sec. cor. of Sec. 7 only, with brass cap marked
	$\frac{1}{4}$ <u>S7</u> 1919
	from which
	A Cedar, 20 ins. diam., bears N.5*E., 72 lks. dist., marked $\frac{1}{4}$ S 7 B T.
	A Hemlock, 12 ins. diam., bears N.29*W., 39 lks. dist., marked $\frac{1}{4}$ S 7 B T.
	Continue descent of NE slope 120 ft. to
42.10	Creek, 2 lks. wide, course NW; ascend SW slope 375 ft. to
64.00	Top of ridge, bears NE and SW; descend SE slope.
74.92	The cor. of Secs. 17 and 18.
	Thence along the S bdy. of Sec. 7.
80.00	(A point due South of the cor. of Secs. 5, 6, 7 and 8)