

SUBDIVISIONS, T. 21 S., R. 10 W.

CHAINS

A Fir, 40 ins. diam., bears N.32*W., 80 lks.
dist., marked T 21 S R 10 W S 6 B T.

Thence

South, on a true line. bet. Secs. 7 and 8.

Over mountainous land, through heavy timber and dense
undergrowth, ascending NW slope 545 ft. to

18.80 Top of ridge, bears NW and SE; descend SW slope 410 ft.
to

29.35 Stream, 1 lk. wide, course W; ascend NW slope 305 ft. to

38.30 Top of spur, slopes W; descend SW slope 105 ft. to

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in
the ground, for $\frac{1}{4}$ Sec. corner, with brass cap marked

$\frac{1}{4}$
S7 | S8
1919

from which

A Fir, 30 ins. diam., bears N.88*E., 18 lks.
dist., marked $\frac{1}{4}$ S 8 B T.

A Cedar, 14 ins. diam., bears N.63*W., 42 lks.
dist., marked $\frac{1}{4}$ S 7 B T.

Continue descent 90 ft. to

42.40 Creek, 3 lks. wide, course W; ascend general N slope
640 ft. to

58.00 Top of ridge, bears NE and SW; descend S slope 60 ft. to

60.00 Foot of descent; ascend along E slope 140 ft. to

67.50 Top of ascent on E slope; descend SE slope 350 ft. to

78.30 (A point due W. of the cor. of Secs. 8, 9, 16 and 17)

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in
the ground, for cor. of Secs. 8 and 17, with brass
cap marked

T21S
S8
S17
R10W
1919

from which