

County Surveyor's Record, ⁷¹Douglas County, Oregon

Subdivisions of T. 22 S., R 4 W., W.M., as surveyed by Wm. P. Wright, U.S. Deputy Surveyor, under Contract No. 514, dated August 27, 1884.

CHAINS	
	West on random line bet. secs. 10 and 15. Va. $21\frac{1}{2}^*E.$
40.00	Set temp. qr. sec. cor.
79.50	Intersect N and S line, 75 lks. N of cor. to secs. 9, 10, 15 and 16, which is a post, 5 ins. diam., in ground marked T 22 S S 10 on NE., R 4 W S 15 on SE., S 16 on SW., S 9 on NW face, from which A Fir, 26 ins. diam., bears S.28*W., 38 lks. dist., marked T 22 S R 4 W S 16 B T. A Fir, 10 ins. diam., bears N.78*W., 22 lks. dist., marked T 22 S R 4 W S 9 B T. A Fir, 14 ins. diam., bears N.60*E., 30 lks. dist., marked T 22 S R 4 W S 10 B T. A Fir, 8 ins. diam., bears S.18*E., 42 lks. dist., marked T 22 S R 4 W S 15 B T. N.89*28'E., on true line bet. secs. 10 and 15. Ascend 30* slope.
25.00	Ascend. 35*slope.
30.00	Ascend 22* slope.
39.75	Set post, 4 ins. diam., 4 ft. long, with marked stone 12 ins. in ground for qr. sec. cor., marked $\frac{1}{4}$ S on N face from which A Maple, 12 ins. diam., bears S.2*E., 61 lks. dist., marked $\frac{1}{4}$.S B T. A Fir, 40 ins. diam., bears N.39*W., 35 lks. dist., marked $\frac{1}{4}$ S B T.
	Still ascend, 32*
67.00	Descend 33*
79.50	The cor. to secs. 10, 11, 14 and 15. Land very rough and mountainous. Soil 2nd rate, dense fir timber. Thick undergrowth of hazel, 79.50 chs. Oct. 16, 1884