

Resurvey of W. Bdy. of T. 22 S., R. 6 W., W. M.

CHAINS

42.50 Ravine, course NW., 25 ft. below $\frac{1}{2}$ sec. cor; ascend spur.

49.00 Top of spur, slopes N.70*W., 150 ft. above last ravine; descend.

58.00 Ravine, course W., 100 ft. below top of last spur.

63.25 Top of spur, slopes W., 150 ft. above ravine, leave green timber, bears E. and W.; Descend.

84.60 Intersect 5th Standard Parallel South, at a point from which the standard cor. of Tps. 23 S., Rs., 6 and 7 W., bears S.89*54'E., 690 chs. dist; and from which the cor. set to refer to T. 23 S R 6 and 7 W., by running from the S., bears S.89*54'E., 175 lks. dist.

The standard Tp. cor., I established Nov. 24, 1897.

The cor. 175 lks. E. of my intersections, which was established after the manner of a closing cor., is a post, 4 ins. sq., 24 ins. above ground, mkd. T 23 S R 6 W S 6 on SE., and R 7 W S 1 on SW faces; with 6 notches on S, E & W edges, from which

Bearing trees agree with the description furnished by the surveyor general.

At point of intersection, I set a Fir post, 3 ft. long, 5 ins. sq., 24 ins. in the ground, for a closing cor. of Tps. 22 S., RS. 6 and 7 W., mkd. C C T 22 S on N., R 6 W S 31 on E., R 7 W S 35 on W. faces; with 6 grooves on the N, E & W. faces; from which

A dead Fir, 20 ins. diam, bears N.20*E., 42 lks. dist. mkd. T 22 S R 6 W S 31 B T.

A dead Fir, 30 ins. diam, bears N.53 $\frac{1}{2}$ *W., 177 lks. dist. mkd. T 22 S R 7 W S 36 B T.

This closing Tp. cor. is 375 ft. below top of spur, last noted.

Land, mountainous.

Soil, 3rd rate.

Timber, Fir, Cedar, Hemlock, Maple, Madrona, and Dogwood.