

Resurvey of 5th Standard Parallel S., through Rs. 6 & 7 W.

CHAINS

- East, on a blank line, along the N. Bdy. of sec. 1, T. 23 S., R. 7 W., and the N. Bdy. of sec. 6 T 23 S R 6 W, setting temporary stakes at intervals of 40.00 chains.
- Difference bet. measurements of 119.60 chs. by two sets of chainmen, is 48 lks; position of middle point.
- By first set, 119.84 chs.
- By second set, 119.36 chs., the mean is
- 119.60 To a point, 21 lks. N. of the standard $\frac{1}{2}$ sec. cor. on the N. Bdy. of sec. 6.
- Difference bet. measurements of 160.20 chs. by two sets of chainmen, is 60 lks; position of middle point.
- By first set, 160.50 chs.
- By second set, 159.90 chs; the mean of which is
- 160.20 To a point, 31 lks N. of the standard cor. of secs. 5 and 6, T. 23 S., R 6 W., which I reestablish at same point from the bearing trees, which I find standing as follows:
- Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for a standard cor. of sec. 5 and 6, mkd. S C T 23 S R 6 W on S., S 5 on E., and S 6 on W. faces; with 5 grooves on E. and 1 groove on W. faces; from which
- A Fir, 28 ins. dia., bears S.25*E., 8 lks. dist. mkd. T 23 S., R 6 W S 5 B T.
- A Fir, 30 ins. dia., bears S.32*W., 25 lks. dist., mkd. T 23 S R 6 W S 6 B T.
- This standard cor. is on the NE. slope of spur.
- Thence I run
- N.89*51*W., on a true line along the N. Bdy. of sec. 6. Mag. decl. 20*45'E.
- Ascend spur.
- 9.50 Top of spur, slopes N.70*W., 150 ft. above standard sec. cor; descend.
- 12.50 Bottom of canyon, course N.50 ft. below top of last spur; ascend spur.