

Resurvey of 5th Standard Parallel S., through Rs. 6 and 7 W.

CHAINS

- 16.75 Top of spur, slopes N, 75 ft. above canyon bottom; ascend spur.
- 18.00 Top of spur, slopes N., 25 ft. above last spur; descend.
- 33.25 Ravine, course N., 50 ft. below top of last spur; ascend spur.
- 34.75 Top of spur, slopes N., 30 ft. above ravine; descend.
- 36.90 Creek, 1 lk. wide, course NW., 25 ft. below top of last spur, ascend spur.
- 40.60 Top of spur; slopes N., 50 ft. above last creek.
To the standard $\frac{1}{2}$ sec. cor. on the N. Bdy. of sec. 6; cor. destroyed. I reestablish this cor. from the bearing tree bearing S.57*E., from the cor. 22 lks. dis. as follows:
Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for a standard $\frac{1}{4}$ sec. cor., mkd. S C $\frac{1}{4}$ S on S. face; from which
A Fir, 24 ins. dia., bears S.57*E., 22 lks. dist. mkd. S C $\frac{1}{4}$ S B T.
An Alder, 7 ins. dia., bears S.7*W., 91 lks. dist. mkd. S C $\frac{1}{4}$ S B T.
From this cor., I run, on true line, N.89*54*W., on the N. Bdy. of sec. 6.
Descend.
- 53.10 Foot of descent, bears NE and SW; enter bottom land.
- 54.32 Creek, 12 lks. wide, course SW., 75 ft. below standard $\frac{1}{2}$ sec. cor.
- 55.84 Trail, bears NE And SW; leave bottom land and ascend; foot of ascent, bears NE and SW.
- 62.60 Leave green timber, bears N. and S.
- 73.00 Top of spur, slopes S.30*W., 75 ft. above foot of ascent; descend.
- 80.47 Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for standard cor. of Tps. 23 S., Rs. 6 and 7 W. mkd. S C T 23 S on S., R 6 W S 6 on E., and R 7 W S 1 on W. faces; with 6 grooves on S. E. and W. faces; from which