

Resurvey of 5th Standard Parallel S., through Rs. 6 and 7 W.

CHAINS	
39.87	<p>Set a madrona post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for standard <math>\frac{1}{4}</math> sec. cor. marked S C <math>\frac{1}{4}</math> S on the N face; from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N.84*W., 32 lks. dist., marked S C <math>\frac{1}{4}</math> S B T.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S.40*W., 12 lks. dist., marked S C <math>\frac{1}{4}</math> S B T.</p> <p>This cor. is on the SE slope of spur, 150 ft. above creek.</p>
44.00	Enter green timber, bears N and S.
48.25	Top of spur, slopes NE 150 ft. above standard $\frac{1}{4}$ sec. cor; descend.
57.77	Creek, 1 lk. wide, course NE 50 ft. below top of spur last noted; ascend spur.
61.25	Top of spur, slopes NE 150 ft. above last creek; descend.
64.70	Creek, 1 lk. wide, course NE 50 ft. below top of last spur; ascend spur.
68.75	Top of spur, slopes NE 75 ft. above last creek; descend.
73.46	Creek, 1 lk. wide, course NE 50 ft. below top of last spur; ascend spur.
79.00	Top of spur, slopes NE 200 ft. above last creek.
79.74	<p>The standard cor. of secs. 1 and 2, T 23 S., R. 7 W., which I reestablish at the same point, as follows:</p> <p>Set a madrona post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for standard cor. of secs. 35 and 36, T. 22 S., R. 7 W., marked S C T 22 S R 7 W on N., S 36 on E., and S 35 on W faces, with 1 groove on E and 5 grooves on W faces; from which</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N.15*E., 25 lks. dist., marked T 22 S R 7 W S 36 B T.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N.18*W., 19 lks. dist., marked T 22 S R 7 W S 35 B T.</p> <p>This cor. is on the Northerly slope of spur.</p> <p>From this cor., the closing cor. of secs. 1 and 2, T. 23 S., R. 7 W., bears West 567 chs. dist.</p> <p>Note:-The standard cors. along the N bdy. of T. 23 S.,</p>