

Subdivisions of T. 22 S., R. 6 W., W. M.

CHAINS	
12.25	Top of spur, slopes NE., 175 ft. above last ravine; descend.
16.00	Ravine, course E., 50 ft. below top of last spur; ascend spur.
18.50	Top of spur, slopes E. 50 ft. above last ravine; descend.
21.75	Ravine, course E. 50 ft. below top of last spur, ascend ridge.
25.00	Top of ridge, bears NW and SE., 75 ft. above ravine; descend.
40.00	Set a sandstone, 12x10x6 ins., 8 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ on W. face, from which A Hemlock, 14 ins. diam., bears N.45*E., 16 lks. dist. mkd. $\frac{1}{4}$ S B T. A Cedar, 20 ins. diam., bears S.31*W., 11 lks. dist. mkd. $\frac{1}{4}$ S B T.
	This $\frac{1}{4}$ sec. cor. is on a SE slope, 175 ft. below top of ridge.
41.45	Creek, 2 lks. wide, course N.60*E., 25 ft. below $\frac{1}{4}$ sec. cor; ascend spur.
42.75	Top of spur, slopes N.60*E., 50 ft. above creek; descend.
44.25	Ravine, course NE., 25 ft. below top of last spur; ascend spur.
50.75	Top of spur, slopes E., 100 ft. above ravine; descend.
61.21	Creek, 1 lk. wide, course E. 75 ft. below top of last spur; ascend spur.
66.25	Top of spur, slopes E., 50 ft. above creek; descend.
69.40	Ravine, course NE., 75 ft. below top of last spur; ascend spur.
71.25	Top of spur, slopes NE., 25 ft. above ravine; descend.
72.36	Creek, 1 lk. wide, course NE., 25 ft. below top of spur; ascend ridge.
78.70	Top of ridge, bears E and W., 175 ft. above creek; trail lies along top of ridge; descend.
86.20	Intersect 5th Standard Parallel South, 8.36 chs. N.89*48*W., of the standard cor. of secs. 3 and 4, which I established November 28, 1897.