

Subdivisions of T. 22 S., R. 6 W., W. M.

CHAINS	
	Thence I run South, 0°1'E., on a true line, bet. secs. 32 and 33. Mag decl. 20°E. Descend.
6.24	Creek, 1 lk. wide, course NE., 35 ft. below sec. cor; ascend spur.
9.25	Top of spur, slopes E., 50 ft. above last creek; descend.
15.97	Creek, 1 lk. wide, course NE., 50 ft. below top of last spur; ascend spur.
20.25	Top of spur, slopes NE., 75 ft. above creek, descend.
22.00	Ravine, course N.10°W., 50 ft. below top of last spur; ascend ridge.
30.00	Top of ridge, bears E. and W., 200 ft. above last ravine; descend.
33.25	Ravine, course E., 50 ft. below top of ridge; ascend spur.
37.50	Top of spur, slopes NE., 75 ft. above ravine; gradually ascend along E. slope of spur.
40.00	Set a sandstone, 16x12x8 ins., 11 ins. in the ground, for $\frac{1}{4}$ sec. cor. mkd. $\frac{1}{4}$ on W. face; from which A Fir, 12 ins. diam., bears N.13 $\frac{1}{2}$ °W., 27 lks. dist. mkd. $\frac{1}{4}$ S B T. A Fir, 20 ins. diam., bears S.45°E., 52 lks. dist. mkd. $\frac{1}{4}$ S B T.
45.25	Top of ridge, bears NW and SE, 35 ft. above last spur; descend.
75.25	Ravine, course SW., 250 ft. below top of ridge; ascend spur.
79.50	Top of spur, slopes SW, 100 ft. above last ravine; descend.
82.50	Ravine, course SW. 50 ft. below top of spur; ascend.
85.62	Intersect 5th Standard Parallel South at a point which bears N.89°48'W., 9.24 chs. dist. from the standard cor. of secs. 4 and 5, which I established Nov.28,1897. At point of intersection, I Set a sandstone 16x8x8 ins. 11 ins. in the ground, for a closing cor. of secs. 32 and 33 mkd. C C on N. with 2