

Subdivisions of T. 22 S., R. 7 W., W. M.

CHAINS	
	<p>At point of intersection, 374 lks. South of this cor., I Set a Sandstone, 12x10x5 ins., 8 ins. in the ground, for a closing corner of secs. 35 and 26, mkd. C C on E., with one groove on S. and 2 grooves on E. faces; from which</p> <p style="padding-left: 40px;">A Fir, 24 ins. diam., bears N.67$\frac{1}{2}$*W., 135 lks. dist. mkd. T 22 S R 7 W S 26 B T.</p> <p style="padding-left: 40px;">A Fir, 10 ins. diam., bears S.35*E., 37 lks. dist. mkd. T 22 S R 7 W S 35 B T.</p> <p>Thence I run East, on a true line, bet. secs. 26 and 35. Descend.</p>
2.35	Ravine, course N., 25 ft. below closing cor.; ascend spur.
4.45	Top of spur, slopes N., 25 ft. above last ravine; descend.
8.60	Ravine, course N., 25 ft. below top of last spur; ascend spur.
10.00	Top of spur, slopes N., 20 ft. above ravine; descend.
10.76	Creek, 1 lk. wide, course N.60*W., 25 ft. below top of last spur; ascend.
29.30	Spur, slopes N., 75 ft. above creek.
33.50	Top of spur, slopes N., 25 ft. below top of last spur; continue descent.
38.80	Creek, 3 lks. wide, course NW., 50 ft. below top of last spur; ascend ridge.
46.84	Set a Hemlock post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ S on N. face; from which <p style="padding-left: 40px;">A Fir, 18 ins. diam., bears N.2*E., 24 lks. dist. mkd. $\frac{1}{4}$ S B T.</p> <p style="padding-left: 40px;">A Fir, 16 ins. diam., bears S.60*W., 34 lks. dist. mkd. $\frac{1}{4}$ S B T.</p> <p>This cor. is on the Westerly slope of mountain, 75 ft. above creek.</p>
53.60	Top of ridge, bears NE. and SW., 150 ft. above $\frac{1}{4}$ sec. cor; descend.