

## Subdivisions of T. 22 S., R. 7 W., W. M.

## CHAINS

I find the cor. of secs. 23, 24, 25 and 26 in a delapidated condition, and reestablish same to refer to the secs. on the North only, from the bearing tree in sec. 23, as follows:

Set a Sandstone, 14x8x6 ins., 9 ins. in the ground for cor. of secs. 23 and 24, mkd. with 1 notch on E. edge; from which

A Maple, 5 ins. diam., bears N.25\*W., 15 lks. dist. mkd. T 22 S R 7 W S 23 B T.

A Fir, 6 ins. diam., bears N.31½\*E., 44 lks. dist. mkd. T 22 S R 7 W S 24 B T.

From this cor., I run

East, on a random line, bet. secs. 24 and 25.

40.00 Set a temp. ¼ sec. cor.

80.00 Intersect West Bdy. of T. 22 S R 6 W., 404 lks. S. of the cor. of secs. 19 and 30, which I set Nov. 25 1897.

At point of intersection, I

Set a Sandstone, 12x8x8 ins., 8 ins. in the ground, for closing cor. of secs. 24 and 25, mkd. C C on W., with 2 grooves on N. faces; from which

A Maple, 5 ins. diam., bears S.68\*W., 46 lks. dist. mkd. T 22 S R 7 W S 25 B T.

A Cedar, 14 ins. diam., bears N.8\*W., 57 lks. dist. mkd. T 22 S R 7 W S 24 B T.

Thence, I run

West, on a true line and establish random as true line.

Ascend spur.

6.75 Top of spur, slopes N., 200 ft. above closing cor.; descend into canyon.

13.00 Bottom of canyon, bears N. and S., 100 ft. below top of last spur; ascend spur.

17.50 Top of spur, slopes N., 100 ft. above canyon; descend.

34.27 Creek, 1 lk. wide, course NW., 150 ft. below top of last spur; ascend spur.

39.00 Top of spur, slopes N.20\*W., 25 ft. above last creek; descend.