

Subdivisions of T. 22 S., R. 7 W., W. M.

CHAINS

furnished by the Surveyor General, their bearings and distances from the cor.; varying materially from that description; at same point, I reestablish this cor. as follows:

Set a Fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for cor. of secs. 33 and 34, T. 21 S., R. 7 W., marked T 21 S S 34 on NE., and R 7 W S 33 on NW faces; with 3 notches on E. and W. edges, from which

A Maple, 10 ins. diam., bears N.33*E., 38 lks. dist. mkd. T 21 S R 7 W S 34 B T.

A Fir, 16 ins. diam., bears N.60*W., 28 lks. dist. mkd. T 21 S R 7 W S 33 B T.

At point of intersection, 5.10 chs. W. of this cor., I

Set a Dogwood post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for a closing cor. of secs. 3 and 4, mkd. C C T 22 S R 7 W on S., S 3 on E., and S 4 on W. faces; with 3 grooves on E. and W. faces; from which

A Fir, 48 ins. diam., bears S.20*E., 57 lks. dist. mkd. T 22 S R 7 W S 3 B T.

A Dogwood, 12 ins. diam., bears S.42*W., 63 lks. dist. mkd. T 22 S R 7 W S 4 B T.

Thence, I run

South, 0*1'E., on a true line bet. secs. 3 and 4.

Descend.

29.34 Creek, 1 lk. wide, course W., 400 ft. below closing cor.; ascend spur.

32.50 Top of spur, slopes W., 100 ft. above creek; ascend ridge.

42.13 Set a Fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground, for $\frac{1}{4}$ sec. cor., mkd. $\frac{1}{4}$ S on W. face; from which

A Fir, 20 ins. diam., bears N.87*E., 40 lks. dist. mkd. $\frac{1}{4}$ S B T.

A Fir, 14 ins. diam., bears S.55 $\frac{1}{2}$ *W., 29 lks. dist. mkd. $\frac{1}{4}$ S B T.