

County Surveyor's Record, Douglas County, Oregon

Portion of W. Bdy. of T. 22 S., R. 8 W.

CHAINS

30.75	Leave same, course NE. & SW.	
31.00	Scotts burg road, course SW.	
36.00	Begin ascent.	
40.00	Set a granite stone, 18x10x6 ins. in ground for cor. to Secs. 7, 12, 13 & 18, from which An alder, 10 ins. diam., bears N.47*W. dist. 181 lks. No other trees near. Land, level bottom; first rate.	+ 50
North, on true line bet. Secs. 7 & 12. Var. 20*E.		
13.00	Top of ridge, course NW. & SE.	+600
13.00	Enter timber.	
29.50	A creek, 5 lks. wide, course SE.	
40.00	Marked a fir, 12 ins. diam. for $\frac{1}{4}$ sec. cor., from which A fir, 10 ins. diam., bears S.30*E. dist. 11 lks. A fir, 12 ins. diam., bears N.50*W. dist. 20 lks.	+300
62.00	A creek, 5 lks. wide, course SE.	
80.00	Set a fir post, 44 ins. long, 5 ins. diam., 18 ins. in ground for cor. to Secs. 1, 6, 7 & 12, from which A fir, 48 ins. diam., bears N.32*E. dist. 24 lks. A fir, 20 ins. diam., bears S.64*E. dist. 47 lks. A fir, 12 ins. diam., bears S.37*W. dist. 42 lks. A fir, 36 ins. diam., bears N.45*W. dist. 6 lks. Land, hilly, 2nd rate. Timber, principally fir, 1st rate.	
North, on true line bet. Secs. 1 & 6. Var. 19 $\frac{1}{2}$ *E.		
16.75	A creek, 2 lks. wide, course E.	
36.50	A creek, 2 lks. wide, course E.	
40.00	Set a fir post, 40 ins. long, 5 ins. diam. for the $\frac{1}{4}$ sec. cor., from which	