

Exterior and Subdivision Lines of T. 22 S. R. 9 W.

CHAINS		
	Land, hilly, broken, third rate. Timber, principally Fir. Underbrush, same and Hazel.	
	West, on true line, between secs. 13 and 24. Va. 19°E.	
15.50	Top of spur, Course N. Enter burned timber.	- 200
40.00	Enter green timber, set a post $\frac{1}{2}$ sec. corner, from which, A Fir, 12 ins. diam., bears North, 74 lks. dist. A Fir, 30 ins. diam., bears S.65°E., 9 lks. dist.	
60.00	A creek, 40 lks. wide, Course N.	- 400
64.25	A Fir, 60 ins. diam.	- 200
80.00	Set a stone 18 x 10 x 8 for corner to secs. 13, 14, 23 and 24, from which, A Fir, 30 ins. diam., bears N.55°E., 32 lks. dist. A Fir, 36 ins. diam., bears S.23°E., 8 lks. dist. A Fir, 20 ins. diam., bears S.43°W., 31 lks. dist. A Fir, 24 ins. diam., bears N.31°W., 68 lks. dist.	
	Land, rolling, second rate. Timber, principally Fir, good. Creek has ample water for mill.	
	North, on true line, between secs. 13 and 14. Va. 19°E.	
2.50	Top of spur, Course E.	+ 100
25.00	Foot of hill	- 500
27.25	South bank of river. Set a meander post, from which, An Ash, 10 ins. diam., bears S.33°E., 30 lks. dist. A Willow, 5 ins. diam., bears S.20°W., 9 lks. dist.	
	Across river, N.75°E., 2.00 chs. Angle opposite 18° distance over 6.46.	
33.71	To right bank of river.	