

County Surveyor's Record, Douglas County, Oregon

Exterior and Subdivision Lines of T. 22 S., R. 9 W.

CHAINS		
	West, on true line, between secs. 16 and 21. Va. 19*E.	
2.00	A spring branch, Course S.80*W.	- 50
36.00	A creek, 3 lks. wide, Course N.	- 400
40.00	Set stone 16 x 12 x 5,8 ins. in ground, for the $\frac{1}{4}$ sec. corner, from which, A Fir, 14 ins. diam., bears N.30*E., 28 lks. dist. A Maple, 12 ins. diam., bears S.15*E., 8 lks. dist.	
54.50	A creek, 5 lks. wide, Course N.	
66.50	A creek, 3 lks. wide, Course NE.	
73.00	A creek, 1 lk. wide, Course S.80*E.	
80.00	Set a Maple post, 40 ins. long, 5 ins. diam., 12 ins. in ground, for corner to secs. 16, 17, 20 and 21, from which, A Maple, 6 ins. diam., bears N.45*E., 38 lks. dist. A Maple, 8 ins. diam., bears S.78*E., 34 lks. dist. A Fir, 24 ins. diam., bears S.40*W., 34 lks. dist. A Fir, 60 ins. diam., bears N.45*W., 45 lks. dist.	
	Land, mountainous, third rate. Timber, principally, Fir. Underbrush, same, and mountain Balm.	
	North, on line between secs. 16 and 17. Va. 19*E.	
1.50	A creek, 1 lk. wide, Course E.	
10.00	Begin descent.	
27.00	Enter bottom, Course E. and W.	- 600
30.00	South bank of the Umpqua river. Set Maple, 40 ins. long, 5 ins. diam., 18 ins. in ground, for meander post, from which, A Maple, (double) 60 ins. diam., bears S.60*E., 30 lks. dist. A Fir, 30 ins. diam., bears S.55*W., 46 lks. dist.	
	Across river, base West, 20.00chs.	
	Angle opposite, 17*. Distance over 6.54.	
36.54	To North bank of river.	