

Exterior and Subdivision Lines of T. 22 S., R. 9 W.

CHAINS
 80.00 Set a Maple post, 36 ins. long, 5 ins. diam., 12 ins. in ground, for corner to secs. 7, 8, 17 and 18, from which,
 A Fir, 60 ins. diam., bears N.22*E., 19 lks. dist.
 A Fir, 72 ins. diam., bears S.65*E., 46 lks. dist.
 A Maple, 24 ins. diam., bears S.40*W., 16 lks. dist.
 A Maple, 30 ins. diam., bears N.10*W., 50 lks. dist.
 Land, mountainous, third rate.
 Timber, Fir, Maple, and Alder.
 Underbrush, same.

West, on true line, between secs. 7 and 18.

Va. 19*E.

8.00 Intersect river, set Ash post, 4 ins. long, 5 ins. diam., 20 ins. in ground, from which,
 A Cottonwood, 8 ins. diam., bears South, 56 lks. dist.
 An Ash, 6 ins. diam., bears N.80*W., 20 lks. dist.
 Across river, base North 200chs.
 Angle opposite, 8*. Distance across 14.23.

- 50

22.23 To right bank of river.
 Land, nearly level, good second rate.
 Timber, principally Fir.

North, between sec. 7 and 8.

Va. 19*E.

33.00 Intersect river. Set Alder post, 40 ins. long, 5 ins. diam., 6 ins. in ground. Stone mound, from which,
 An Alder, 5 ins. diam., bears East, 40 lks. dist.
 An Alder, 7 ins. diam., bears S.2*W., 25 lks. dist.
 Across river, base N.68*E., 2.00 chs.
 Angle opposite, 17*. Across 6.81.

39.81 To right bank of river.
 Land, nearly level, first rate.