

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 22 S., R. 9 W.

CHAINS	
	A Fir, 6 ins. diam., bears S.23*E., 55 lks. dist., Mark T. 22 S., R. 9 W., S. 12 B. T.
	A Maple, 24 ins. diam., bears S.40*W., 15 lks. dist., Mark T. 22 S., R. 9 W., S. 11 B. T.
	A Fir, 10 ins. diam., bears N.65*W., 51 lks. dist., Mark T. 22 S., R. 9 W., S. 2 B. T.
	Thence, I run, N.0*01'W., between secs. 1 and 2.
	Va. 20*30'E.
1.75	Pass over spur, Course W.
4.00	A creek, 1 lk. wide, Course W. Gradual descent.
12.25	Pass over spur, Course W.
14.50	A creek, 1 lk. wide, Course W.
16.50	A creek, 2 lks. wide, Course W.
32.00	Spur, Course W.
33.50	A creek, 1 lk. wide, Course W.
40.00	Set Fir post, 4½ feet long, 4 ins. square, 24 ins. in ground, on hillside sloping W., for ¼ sec. corner. Marked ¼ S. on the West face, from which, A Fir, 12 ins. diam., bears N.21*30'E., ³² 30 lks. dist., Marked ¼ S. B. T. A Fir, 24 ins. diam., bears N.54*W., 61 lks. dist., Marked ¼ S. B. T.
46.70	A creek, 1 lk. wide, Course W. Pass over spur.
55.05	A creek, 2 lks. wide, Course W.
62.00	Spur, Course W.
63.00	A creek, 1 lk. wide, Course W.
77.66	Intersected the N. Bdy. of T., 120 lks. W. of the corner to secs. 1, 2, 35 and 36, T. 21 S., which is a post, 2 feet above ground, 4 ins. square, firmly set.

- 100

For research
18-97 D.C.S.O.
JC

+ 100