

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 82 S., R. 9 W.

CHAINS

Underbrush, dense, thimbleberry, salmonberry, salalberry, hazel, and fir. 77.66 chs.

October 15, 1894.

Commenced at the corner to secs. 2, 3, 10 and 11, I re-established this corner, as follows:

40.00 North of the $\frac{1}{4}$ sec. corner, between secs. 10 and 11.

Set Hemlock post, $4\frac{1}{2}$ feet long, 5 ins. square, 24 ins. in the ground, on steep hillside sloping NE.

Marked T 22 S S 2 on the NE., R 9 W S 11 on the SE., S 10 on the SW., and S 3 on the NW., faces with 5 notches on S. and 2 notches on the E. edges, from which An Alder, 20 ins. diam., bears N.9°E., 62 lks. dist.

Marked T 22 S R 9 W S 2 B T.

A Maple, 14 ins. diam., bears S.11°30'E., 49 lks. dist.

Marked T 22 S R 9 W S 11 B T.

A Fir, 30 ins. diam., bears S.38°W., 34 lks. dist.

Marked T 22 S R 9 W S 10 B T.

A Maple, 16 ins. diam., bears N.30°30'W., 27 lks. dist.

Marked T 22 S R 9 W S 3 B T.

Thence, I run

North, 0°02'W., on Random line, between secs. 2 and 3.

Va. 20°E.

40.00 Set temporary $\frac{1}{4}$ sec. corner.

75.50 Intersected North Bdy. of T., 18 lks. West of the cor. to secs. 2, 3, 34 and 35, which is a post, 2 feet long, 4 ins. square, firmly set.

Marked T 21 S S 35 on the NE., R 9 W S 2 on the SE., T 22 S S 3 on the SW., and S 34 on the NW. faces with 2 notches on the E., and 4 notches on the W. edges, from which