

Subdivisions of T. 22 S., R. 9 W.

CHAINS

Commenced at the corner to secs. 9, 10, 15 and 16, which
I re-established by running,

North, 47.43 chs. from the meander corner between secs.
15 and 16, on the right bank of the Umpqua river.

Set sand stone, 20 x 16 x 6 ins., 15 ins. in the ground,
on hillside sloping S.

Marked with 4 notches on the S., and 3 notches on the E.
edges, from which,

A Cedar, 10 ins. diam., bears N.81°E., 39 lks. dist.

Marked T. 22 S., R. 9 W., S. 10 B. T.

A Fir, 48 ins. diam., bears S.51°E., 145 lks. dist.

Marked T. 22 S., R. 9 W., S. 15 B. T.

A Maple, 20 ins. diam., bears S.44°30'W., 22 lks. dist.

Marked T. 22 S., R. 9 W., S. 16 B. T.

A Maple, 4 ins. diam., bears N.13°W., 40 lks. dist.

Marked T. 22 S., R. 9 W., S. 9 B. T.

Note: I found blazing on E. and W. line corresponding
with this corner.

Thence, I run,

N.1°W., between secs. 9 and 10.

Va. 20°E.

- 5.60 Trail Course, E. and W. and enter land slide.
- 7.10 A creek, 2 lks. wide, Course E.
- 10.50 Leave land slide, Course E.
- 17.00 To margin of small lake, caused by land slide. Thence,
I offset W. 2.85 chs, thence, on offset line, N.0°1'W.,
14.85 chs., offset, E. 285 lks. to line, thence, I
run, S.0°1'E., 5.00 chs. to margin of lake.
- 26.85 Thence, I run North 0°1'W.
- 40.00 Set Maple post, 4½ feet long, 4 ins. square, 24 ins. in
ground on hillside sloping W. for ¼ sec. corner, marked
¼ S. on W. face, from which,