

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 22 S., R. 9 W.

CHAINS		
	North, 0*4'E., between secs. 4 and 5.	
	Va. 20*E.	
7.19	A Fir, 40 ins. diam., a line tree marked with 2 notches on the N. and S. sides.	
28.00	Summit of spur, Course W. Descend.	+ 100
39.50	Canyon, Course, N, 75*W. Ascend.	- 200
40.00	Set sand stone 12 x 10 x 8 ins., 9 ins. in the ground on steep hillside sloping S. for $\frac{1}{2}$ sec. corner, marked $\frac{1}{2}$ on the W. side, from which, A Fir, 10 ins. diam., bears N.82*E., 21 lks. dist. Marked $\frac{1}{2}$ S. B. T. A Fir, 24 ins. diam., bears S.47*W., 101 lks. dist. Marked $\frac{1}{2}$ S. B. T.	
43.50	Top of spur, Course W. Descend.	+ 75
51.75	Canyon, Course W. Ascend.	- 125
62.50	Ridge, Course E. and W. Descend.	+ 200
70.50	A creek, 1 lk. wide, Course W.	- 150
74.23	Intersected N. Bdy. of T., 9.03 chs., W. of the corner to secs. 32 and 33, T. 21 S., which is a stone 10 x 7 x 13 ins. above ground, firmly set, and marked with 2 notches on the W., and 4 notches on the E. sides, from which, A Chinquapin, 8 ins. diam., bears N.37*E., 50 lks. dist. Marked T. 21 S., R. 9 W., S. 33 B. T. A Fir, 8 ins. diam., bears S.37*E., 104 lks. dist. Marked T. 22 S., R. 9 W., S. 4 B. T. A Fir, 12 ins. diam., bears S.34*30'W., 99 lks. dist. Marked T. 22 S., R. 9 W., S. 5 B. T.	