

Subdivisions of T. 22 S., R. 9 W.

CHAINS		
	Thence, I. run;	
	N.0°3'E., on true line, between secs. 5 and 6,	
3.61	Closing corner to secs 5 and 8.	
	Va. 20°E.	
5.50	A creek, 2 lks. wide, Course E. Ascent.	- 50
7.00	Top of ridge, Course E. and W.	+ 50
32.00	Descend steep hill.	
36.00	A creek, 5 lks. wide, Course NE.	- 100
38.25	Entered land slide, Course E.	
39.25	Leave land slide, Course E.	
40.00	Set sand stone, 12 x 10 x 6 ins., 9 ins. in the ground on steep hillside sloping SE., for $\frac{1}{4}$ sec. corner marked $\frac{1}{4}$ on the W. face, from which, A Fir, 10 ins. diam., bears S.73°E., 18 lks. dist. Marked $\frac{1}{4}$ S. B. T. An Alder, 10 ins. diam., bears N.62°W., 37 lks. dist. Marked $\frac{1}{4}$ S. B. T. Pass over spur.	
54.75	A creek, in land slide, 5 lks. wide, Course SE.	
78.12	Intersected N. Bdy. of T., 314 lks. West of the corner to secs. 31 and 32, T. 21 S., which is a post 2 feet above ground, 4 ins. square, marked T. 21 S., S. 32 on the NE., R. 9 W., S. 5 on the SE., T. 22 S. S. 6 on the SW. S. 31 on the NW. faces with 5 notches on the E. and 1 notch on the W. edges, from which, A Fir, 8 ins. diam., bears N.17°30'E., 157 lks. dist. Marked T. 21 S., R. 9 W., S. 32 B. T. A Fir, 30 ins. diam., bears S.17°30'E., 195 lks. dist. Marked T. 21 S., R. 9 W., S. 5 B. T. A Stump, 20 ins. diam., bears S.44°W., 54 lks. dist. Marked T. 22 S., R. 9 W., S. 6 B. T. A Fir, 30 ins. diam., bears N.81°W., 257 lks. dist. Marked T. 21 S. R. 9 W., S. 31 B. T.	