

County Surveyor's Record, Douglas County, Oregon

Subdivisions of T. 22 S., R. 9 W.

CHAINS

I destroyed marks on post and B. T. on S.

I set stone 12 x 12 x 8 ins., 9 ins. in ground on steep hillside sloping West at the point of intersection for closing corners to secs. 5 and 6, marked C. C. on the S. with 5 marks on the E. and 1 mark on the W. edges, from which,

A Fir, 30 ins. diam., bears S.2°E., 307 lks. dist.

Marked T. 22 S., R. 9 W., S. 5 B. T.

A Fir, 30 ins. diam., bears S. 27°30'W., 90 lks. dist.

Marked T. 22 S., R. 9 W., S. 6 B. T.

A Fir, 36 ins. diam., bears N.17°W., 65 lks. dist.

Marked T. 22 S., R. 9 W., S. 5-6 B. T.

Land, mountainous, 78.12 chs.

Soil, first and second rate.

Timber, Fir, Alder, and Maple.

Undergrowth, dense Thimble and Salalberry, vine-Maple,

Hazel and Fir. 78.12 chs.

October 23, 1894.

Commenced at the corner to secs. 23, 24, 25 and 26,
which I re-established as follows:

Set Fir post, 4½ feet long, 4 ins. square, 24 ins. in the ground, on hillside sloping West, marked T. 22 S., S 24 on the NE. R. 9 W., S. 25 on the SE., S. 26 on the SW and S. 23 on the NW., faces with 2 notches on the S. and 1 notch on the E. edges, from which,

A Fir, 12 ins. diam., bears N.54°E., 67 lks. dist.

Marked T. 22 S., R. 9 W., S. 24 B. T.

An Alder, (stump), S. 77°E., 25 lks. dist.

An Alder, 12 ins. diam., bears S.28°W., 60 lks. dist.

Marked T. 22 S., R. 9 W., S. 26 B. T.

An Alder, 8 ins. diam., bears N.82°W., 37 lks. dist.

Marked T. 22 S., R. 9 W., S. 23 B. T.