

Subdivisions of T. 22 S., R. 9 W.

CHAINS		
	<p>I marked a Fir, 6 ins. diam., bears S.50*E., 47 lks. dist., marked T. 22 S., R. 9 W., S. 24 B. T.</p> <p>Practically agreeing with notes supplied me by the U. S. Surveyor General.</p> <p>Thence, I run, S.0*01'E., between secs. 25 and 26.</p> <p style="text-align: right;">Va. 20*E.</p>	
4.00	A creek, 20 lks. wide, Course NW. Ascend.	
24.00	Pass over spur, Course NE.	
30.00	Top of steep ascent. Thence, along bench.	+ 150
39.25	A Fir, 24 ins. diam., a line tree marked with 2 notches on the N. and S. sides.	
40.00	<p>Set a Fir post, 4½ feet long, 4 ins. square, 24 ins. in the ground on level bench for ¼ sec. corner, marked ¼ Sec. on the West face, from which,</p> <p>A Fir, 30 ins. diam., bears N.88*E., 26 lks. dist.</p> <p>Marked ¼ Sec. B. T.</p> <p>A Fir, 12 ins. diam., bears West, 68 lks. dist.</p> <p>Marked ¼ Sec. B. T.</p>	
52.25	<p>Top of ridge, Course E. and W.</p> <p>Descend gradually.</p>	+ 200
57.00	Began steep descent.	
60.60	A creek, 1 lk. wide, Course SE.	
70.30	Spur slopes, SE.	
80.00	<p>Set Maple post, 4½ feet long, 4 ins. square, 24 ins. in the ground on hillside sloping West for the corner to secs. 25, 26, 35 and 36, marked T. 22 S. S. 25 on the NE., R. 9 W., S 36 on the SE., S. 35 on the SW and S. 26 on the NW., faces with 1 notch on the S., and E. edges, from which,</p> <p>A Fir, 30 ins. diam., bears N.80*E., 68 lks. dist.</p>	