

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 22 S., R. 9 W.

## CHAINS

Marked T. 22 S., R. 9 W., S. 23 B. T.

A Dead Fir, 48 ins. diam., bears S.55\*E., 52 lks. dist.

Marked T. 22 S., R. 9 W., S. 26 B. T.

A dead Fir, 24 ins. diam., bears S.51\*W., 118 lks. dist.

Marked T. 22 S., R. 9 W., S.27 B. T.

A dead Fir, 36 ins. diam., bears N.41\*W., 88 lks. dist.

Marked T. 22 S., R. 9 W., S. 22 B. T.

Thence, I run,

S.0\*02'E., between secs. 26 and 27.

Va. 19\*30'E.

Ascend along hillside sloping nearly West.

23.55 A dead Fir, 28 ins. diam., a line tree, marked with 2 notches on the N. and S. sides.

38.00 Top of ridge and trail, Course E. and W.

+ 500

Descend.

40.00 Set sand stone, 18 x 12 x 8 ins., 13 ins. in the ground for  $\frac{1}{4}$  sec. corner, marked  $\frac{1}{4}$  on the W. side, from which, A Fir, 30 ins. diam., bears S.32\*E., 70 lks. dist.

Marked  $\frac{1}{4}$  S. B. T.

A Fir, 36 ins. diam., bears S. 13\*W., 105 lks. dist.

Marked  $\frac{1}{4}$  S. B. T.

41.50 Enter green timber, Course E. and W.

49.19 A Fir, 50 ins. diam., a line tree, marked with 2 notches on the N. and S. sides.

52.00 A creek, 1 lk. wide, Course SE.

59.00 Spur, Course SE.

67.25 A creek, 1 lk. wide, Course SE.

- 400

74.00 To a point 9.25 chs., S.89\*51'E. of the NE. to secs. 34 and the SE. corner of secs. 27, which I re-established as follows:

Set sand stone, 12 x 8 x 8 ins., 9 ins. in the ground on hillside sloping S. for NE. corner to sec. 34, marked with 2 notches on the E., and 1 notch on the S. side, from which,