

## County Surveyor's Record, Douglas County, Oregon

## Subdivisions of T. 22 S., R. 9 W.

## CHAINS

- 23.00 A creek, 4 lks. wide, Course NE.
- 40.00 Set s and stone, 12 x 10 x 6 ins., 9 ins. in the ground on steep hillside sloping North for  $\frac{1}{2}$  sec. corner, marked  $\frac{1}{2}$  on the W. side, from which,  
A Fir, 36 ins. diam., bears N.17\*E., 20 lks. dist.  
Marked  $\frac{1}{2}$  S. B. T.  
A Fir, 6 ins. diam., bears N.45\*W., 52 lks. dist.  
Marked  $\frac{1}{2}$  S. B. T.
- 42.50 Enter land slide, Course NE.
- 45.00 Leave land slide, Course NE.
- 48.75 Top of ridge and trail, Course E. and W. + 500  
Descend.
- 57.00 Enter green timber, Course E. and W.
- 67.00 A creek, 1 lk. wide, Course S.15\*E.
- 70.00 A creek, 3 lks. wide, Course SE.
- 72.00 A creek, 3 lks. wide, Course S.70\*E.
- 74.40 Intersected E. and W. line, 788 lks., S.89\*51'E. of corner to secs. 33 and 34, which, I re-established, as follows:  
Set Maple post, 4 $\frac{1}{2}$  feet long, 4 ins. square, 24 ins. in the ground, on steep hillside sloping E., marked T. 22 S. S. 34 on the SE., R. 9 W., S. 33 on the SW. faces with 1 notch on the S. and 3 notches on the E. edges, from which,  
A Fir, 40 ins. diam., bears N.15\*E., 141 lks. dist.  
Marked T. 22 S., R. 9 W. S. 27 B. T.  
A Fir, 24 ins. diam., bears S.15\*E., 95 lks. dist.  
Marked T. 22 S., R. 9 W., S. 34 B. T.  
A Fir, 36 ins. diam., bears S.40\*W., 115 lks. dist.  
Marked T. 22 S., R. 9 W., S. 33 B. T.  
A Maple, 10 ins. diam., bears N.80\*W., 77 lks. dist.  
Marked T. 22 S., R. 9 W., S. 28 B. T.  
Only one bearing tree agrees with notes furnished me by the U. S. Survey General. I destroyed the B. T. on N.